GPRINT

G-PRINT

G-Print is a woodfree coated paper. High bulk, generous paper feel and excellent runability, making G-Print a great paper choice. Smooth yet bulky it is noted for its consistent technical quality. The smooth, low-reflecting surface provides both perfect readability and quality image reproduction, with high gloss contrast. G-Print offers sharp, even print and low mottling tendencies. Finishing performance provides unique folding and binding properties. G-Print is ideal for books, magazines, brochures, catalogues, covers, direct mail, folders, posters, inserts and maps. G-Print is available both as sheets and reels in various sizes in grammages from 70 to 300 g/m². G-Print standard products are available as FSC™ and PEFC certified.

BASIC INFORMATION
Optimized for colour printing.
Available in sheets. Available in reels

ENVIRONMENT / SAFETY
The paper is inspected for Nordic Ecolabelled printing , ECF, ISO 14001, EMAS, Paper Profile, Safety of Toys , Woodfree, FSC_C007342, PEFC_053398

PRINTING TECHNIQUES
Offset (heatset), Offset (sheet-fed), Flexo, Laser, HP Indigo

SHADE
White

SURFACE
Coated, Matt

FSC
www.fsc.org
FSC® C007342
The mark of
responsible forestry

PEFC
PEFC/05-33-98
PEFC Certified
www.pefc.org

G-PRINT

Grammage (g/m²)	70	80	90	100	115	130	150	170	200	250	300
Opacity (%)	87.5	90.5	92	93.5	96	97	98	98.5	99	99.5	99.5
Thickness (µm)	68	77	87	98	113	129	150	172	203	255	318
Bulk (thickness/grammage)	0.96	0.96	0.97	0.98	0.98	0.99	1.0	1.01	1.02	1.02	1.06
Whiteness (CIE)	117	117	117	117	117	117	117	117	119	119	119
Brightness (ISO 2470/D65 %)	95	95	95	95	95	95	95	95	97	97	97
Smoothness (PPS, µm)	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.2	2.2	2.8
Surface Gloss (TAPPI T 480: 75°, g.u.)	<25	<25	<25	<25	<25	<25	<25	<25	<30	<30	<30

Screen recommended, max 175 lpi

Values are targets only and can be subject to changes over time without prior notice.