

BillerudKorsnäs Decor LINER

Production Unit: Gävle Mill

Product Description

The light coated Decor kraftliner is a preferred material for high quality post-print.

High strength ensures light, strong packages with minimised washboarding.

BillerudKorsnäs Decor is produced from 100% virgin fibres.

Grammages

120, 145, 160g/m²

Approvals

BillerudKorsnäs Decor is produced in compliance with FDA and BfR packaging norms.

Certification

Gävle mill is certified in accordance with ISO 9001 ISO 14001, ISO 50001 and FSSC 22000

Property	Unit					Method
Grammage	g/m ²		120	145	160	ISO 536
Caliper	Microns		145	180	195	ISO 534
Bursting Strength	kPa		600	750	800	ISO 2759
SCT	kN/m	CD	2,9	3,5	4,0	ISO 9895
Tensile Stiffness	kN/m	MD	980	1250	1300	ISO 1924-3
	kN/m	CD	500	600	700	
Roughness PPS-10 TS	Microns	PS	1,2	1,4	1,5	ISO 8791-4
Gloss	%	PS	45	45	45	TAPPI T480
Brightness	%	PS	80	80	80	ISO 2470
Whiteness D65	%	PS	80	82	82	ISO 11475
Cobb 60	g/m ²	PS	34	34	34	ISO 535
	g/m ²	RS	38	38	38	
Moisture	%		7,0	7,0	7,0	ISO 287

MD = Machine Direction

CD = Cross Direction

PS = Printing Side

RS = Reverse Side

Test climate: 50% RH, 23C

The table shows typical values for a range of products