


PAPELERA DEL PRINCIPADO, S.A.



**Enlace Autovia L-200 Mollerussa-Borges Blanques
25230 - Mollerussa (Lleida)**

Tno: 34-973-600050

Fax: 34-973-603431

STANDARD CHARACTERISTICS COATED DUPLEX BOARD GREY BACK - GD2 - SYROS ESTUCADO R/G

Substance Gr/m ²	Caliper Microns	Taber stiffness		Bulk cm ³ /gr	Moisture %
		S.L.	S.T.		
+/- 5 %	+/- 5 %	+/- 15 %		+/- 5 %	
190	215	2,1	1,1	1,13	6,0/7,3
200	230	3,1	1,4	1,15	6,0/7,3
210	245	3,4	1,7	1,17	6,0/7,3
220	260	4,0	2,0	1,18	6,0/7,3
230	280	4,5	2,0	1,22	6,0/7,3
250	315	7,0	3,1	1,26	6,5/7,8
275	345	9,0	4,1	1,25	6,5/7,8
300	395	12,2	5,5	1,32	6,5/8,0
325	425	15,2	6,9	1,31	6,6/8,1
350	465	19,1	8,6	1,33	6,7/8,2
375	500	23,0	10,2	1,33	6,8/8,3
400	535	27,0	12,3	1,34	7,0/8,5
425	560	31,4	14,8	1,32	7,0/8,5
450	600	36,8	17,3	1,33	7,2/8,7
475	630	42,1	19,6	1,33	7,3/8,8
500	670	47,0	22,1	1,34	7,5/9,0
550	720	49,0	24,5	1,31	8,5/10,5

-Max-Min width: -Sheets: 3.000 mm. - 350 mm. -Reels: 4.700 mm. - 450 mm.	-Max-Min length: -Sheets: 1.600 mm. - 450 mm.
-Max-Min diameter: -Reels: 1.600 mm. - 750 mm.	-Max-Min core: -Reels: 300 mm. - 70 mm.
-Coating: 24/28 Gr/m ²	-Ceras Dennison: More than 6
-Smoothness Bendtsen: less than 50 ml/min	- Brightness white side: 78 / 81 DIN 5033

Mollerussa, January 2018

Doc: 030201f12-Ing